

SAVEL

More Than Technology



Innovation
7 Series
new product

7 SERIES - INNOVATION			Fuel Type	Number of Nozzles	Number of Display	Simultaneous Filling	Suction Sales (USD)	Dispenser Sales (USD)
1	7.24 l	Quad Innovation	2	4	2	2	16.250,00	15.000,00
2	7.36 l	Six Innovation	3	6	2	2	19.900,00	17.900,00
3	7.51 l	Eight Innovation	4	8	2	2	22.400,00	20.400,00
4	7.51 l	Ten Innovation	5	10	2	2	22.900,00	22.900,00

General Features

General

The electronic unit designed with the latest technology
 Manufacture types as suction or pressure
 Relative humidity -30/+80°C and %95 ± Accuracy ± 0,25%

Motor

380 ACV /50 Hz three phases or 220 ACV monophase
 Protected against excessive load, ex-proof, 0.75 kW motor

Meter

All our pumps have adjustable meters which are electronically

Pumping-Unit

Our suction pumps equipped with positive displacement as rotary typed, by-pass valve, air separator, integrated suction filter and V belt driven. Speeds of the flow represents a diversity between 50/80/120 lt/min

Totalizers

12 digits electronics totalizers for liter, money, shift-money and shift-liter, in addition to these, also 7 digits electromechanic totalizers according to your requests.

Electronic Unit

Compatibility with the CANBUS technology
 2 noozles working at the same time
 USB port support
 Programmable electronic card
 RS485 or Current-loop communication option
 Compatibility with all the cash registers
 Compatibility with Savel multimedia module
 Automatic electronic calibration
 Compatibility with all the automation systems
 1-wire and 2-wire special communication system
 Card design according to the EMC tests
 Menu systems in 6 different languages (Tr, En, Fr, Ar, Ru, Ge)
 10 digits for electronic total

Keyboard

Keypad with 16 buttons

Display

1" (25.4 mm) 6 digits for money, 6 digits for liter, 6 digits for unit price. Option one is a single screen.

Nozzle and Hose

3/4 for standart dispensers and 1 for high efficient dispensers. Equally, hoses are 3/4 or 1. We use 360 degree rotating swivels to facilitate the usage.



SAVEL

Perpa Ticaret Merkezi B Blok Kat: 13 No: 2390
 Okmeydanı – İstanbul - TURKEY
 Phone: (212) 210 01 18 Fax: (212) 210 01 19
 info@savel.com.tr www.savel.com.tr

More Than Technology

+ Fuel
 + Automation
 + LPG
 + CNG

5 SERIES - MULTIMEDIA				Fuel Type	Number of Nozzles	Number of Display	Simultaneous Filling	Suction Sales (USD)	Dispenser Sales (USD)
1	5.22 M	Dual	Multimedia	2	2	2	2	12.000,00	11.000,00
2	5.24 M	Quad	Multimedia	2	4	2	2	13.750,00	12.900,00
3	5.36 M	Six	Multimedia	3	6	2	2	17.500,00	15.500,00
4	5.48 M	Eight	Multimedia	4	8	2	2	20.000,00	18.000,00

General Features

General

26 "or 32" LCD and multimedia support
 Durable chassis is made of galvanized steel
 The electronic unit designed with the latest technology
 Manufacture types as suction or dispenser
 To work with -30/+80°C and %95 ± relative humidity
 Accuracy ± 0,25%

Motor

380 ACV /50 Hz three phases or 220 ACV monophase
 Protected against excessive load, ex-proof, 0.75 kW motor

Meter

All our pumps have adjustable meters which are electronically calibrated and typed as positive displacement piston.

Pumping-Unit

Our suction pumps equipped with positive displacement as rotary typed, by-pass valve, air separator, integrated suction filter and V belt driven. Speeds of the flow represents a diversity between 50/90/120 lt/min.

Totalizers

12 digits electronic totalizers for liter, money, shift-money and shift-liter, in addition to these, also 7 digitelectromechanic totalizers according to your requests.

Electronic-Unit

Compatibility with the Can Bus technology
 2 noozles working at the same time
 USB port support
 Programmable electronic card
 RS485 or Current-loop communication option
 Compatibility with all the cash registers
 Compatibility with Savel multimedia module
 Automatic electronic calibration
 Compatibility with all the automation systems
 1-wire and 2-wire special communication system
 Card design according to the EMC tests
 Menu systems in 6 differents languages (Tr, En, Fr, Ar, Ru, Ge)
 10 digits for electronic total

Keyboard

Keypad with 16 buttons

Display

1" (25.4 mm) 6 digits for money, 6 digits for liter, 6 digits for unit price. Option one is a single screen.

Nozzle and Hose

3/4 for standart dispensers and 1 for high efficient dispensers. Equally, hoses are 3/4 or 1. We use 360 degree rotating swivels to facilitate the usage.



SAVEL

Perpa Ticaret Merkezi B Blok Kat: 13 No: 2390
 Okmeydanı – İstanbul - TURKEY
 Phone: (212) 210 01 18 Fax: (212) 210 01 19
 info@savel.com.tr www.savel.com.tr

More Than Technology

- + Fuel
- + Automation
- + LPG
- + CNG

3 SERIES - CLASSIC			Fuel Type	Number of Nozzles	Number of Display	Simultaneous Filling	Suction Sales (USD)	Dispenser Sales (USD)
1	3.12 C	Dual Classic	1	2	2	2	4.320,00	4.040,00
2	3.22 C	Dual Classic	2	2	2	2	5.440,00	4.880,00
3	3.24 C	Quad Classic	2	4	2	2	7.200,00	6.640,00
4	3.36 C	Six Classic	3	6	2	2	10.240,00	8.720,00
5	3.48 C	Eight Classic	4	8	2	2	12.400,00	10.600,00
6	3.51 C	Ten Classic	5	10	2	2		12.800,00

General Features

General

The electronic unit designed with the latest technology
 Manufacture types as suction or dispenser
 To work with -30/+80°C and %95 ± relative humidity
 Accuracy ± 0,25%

Motor

380 ACV /50 Hz three phases or 220 ACV monophase
 Protected against excessive load, ex-proof, 0.75 kW motor

Meter

All our pumps have adjustable meters which are electronically calibrated and typed as positive displacement piston

Pumping-Unit

Our suction pumps equipped with positive displacement as rotary typed, by-pass valve, air separator, integrated suction filter and V belt driven. Speeds of the flow represents a diversity between 50/90/120 lt/min

Totalizers

12 digits electronic totalizers for liter, money, shift-money and shift-liter, in addition to these, 7 digits electromechanic totalizers according to your requests.

Electronic-Unit

Compatibility with the Can Bus technology
 2 noozles working at the same time
 USB port support
 Programmable electronic card
 RS485 or Current-loop communication option
 Compatibility with all the cash registers
 According to Savel multimedia module
 Automatic electronic calibration
 Compability with all the automation systems
 1-wire and 2-wire special communication system
 Card design according to the EMC tests
 Menu systems in 6 differents languages (Tr, En, Fr, Ar, Ru, Ge)
 10 digits for electronic total

Keyboard

Keypad with 16 buttons

Display

1" (25.4 mm) 6 digits for money, 6 digits for liter, 6 digits for unit price. Option one is a single screen.

Noozle and Hose

3/4 for standart dispensers and 1 for high efficient dispensers. Equally, hoses are 3/4 or 1. We use 360 degree rotating swivels to facilitate the usage.



SAVEL

Perpa Ticaret Merkezi B Blok Kat: 13 No: 2390
 Okmeydanı – İstanbul - TURKEY
 Phone: (212) 210 01 18 Fax: (212) 210 01 19
 info@savel.com.tr www.savel.com.tr

More Than Technology

- + Fuel
- + Automation
- + LPG
- + CNG

1 SERIES - BASIC			Fuel Type	Number of Nozzles	Number of Display	Simultaneous Filling	Suction Sales (USD)	Dispenser Sales (USD)
1	1.11 B	Single Electronic	1	1	2	1	3.120,00	2.880,00
2	1.12 B	Dual Electronic	1	2	2	2	4.320,00	4.040,00
3	1.22 B	Dual Electronic	2	2	4	2	5.200,00	4.720,00

General Features

General

Durable chassis is made of galvanized steel
 Manufacture types as suction or dispenser
 To work with -30/+80°C and %95 ± relative humidity
 Accuracy ± 0,25%

Motor

380 ACV /50 Hz three phases or 220 ACV monophase
 Protected against excessive load, ex-proof, 0.75 kW motor

Meter

All our pumps have adjustable meters which are electronically calibrated and typed as positive displacement piston

Pumping-Unit

Our suction pumps equipped with positive displacement as rotary typed, by-pass valve, air separator, integrated suction filter and V belt driven. Speeds of the flow represents a diversity between 50/90/120 lt/min

Totalizers

12 digits electronic totalizers for liter, money, shift-money and shift-liter, in addition to these, also 7 digits electromechanic totalizers according to your requests.

Electronic-Unit

The electronic unit designed with the latest technology
 10 digits for electronic total
 RS485 or Current-loop communication option
 Compatibility with all the cash registers

Keyboard

Keypad with 16 buttons

Display

1" (25.4 mm) 6 digits for money, 6 digits for liter, 6 digits for unit price. Option one is a single screen.

Nozzle and Hose

3/4 for standart dispensers and 1 for high efficient dispensers. Equally, hoses are 3/4 or 1. We use 360 degree rotating swivels to facilitate the usage.



SAVEL

Perpa Ticaret Merkezi B Blok Kat: 13 No: 2390
 Okmeydanı – İstanbul - TURKEY
 Phone: (212) 210 01 18 Fax: (212) 210 01 19
 info@savel.com.fr www.savel.com.fr

More Than Technology

- + Fuel
- + Automation
- + LPG
- + CNG